

Safety Data Sheet

DATE PREPARED: 12/13/2022

DATE UPDATED: 7/11/2024

SECTION 1: Identification

6528 BLACK MIXTURE

Health 2*
Flammability 0
Reactivity 0
Personal Protection See Section 8



Product number 6528 Charcoal

1.4 Supplier's details

Name Mason Color Works Inc.
Address 250 East Second Street
East Liverpool, Ohio 43920
USA
Telephone 330 385 4400
Fax 330 385 4488

SECTION 2: Hazard identification

Signal Word: **WARNING**

GHS classification in accordance with OSHA (29 CFR 1910.1200) Not a hazardous substance
H303: May be harmful if swallowed P261: Avoid breathing dust.
H313: May be harmful in contact with skin P262: Do not get in eyes, on skin.
H317: May cause an allergic skin reaction P264: Wash hands thoroughly after handling.
H333: May be harmful if inhaled
H335: May cause respiratory



SECTION 3: Composition/information on ingredients

| | | | % | EC no. | CAS no. | Index no. | Formula |
|------|-----------------------------------|-----------------------|-----|-----------|------------|------------|-------------------|
| | TIN OXIDE | | 70% | 242-159-0 | 18282-10-5 | | SnO |
| 6600 | IRON COBALT CHROMITE BLACK SPINEL | C.I. Pigment Black 27 | 30% | 269-060-5 | 68186-97-0 | C.I. 77502 | (Co,Fe)(Fe,Cr)2O4 |

•Contact with skin: Wash with plenty of water and soap.
•Contact with eyes: Wash immediately with water for at least 10 minutes.
•Swallowing: SEEK A MEDICAL EXAMINATION IMMEDIATELY and present the safety-data sheet.
A suspension of activated charcoal in water, or liquid paraffin may be administered.
•Inhalation: Ventilate the premises.
The patient is to be removed immediately from the contaminated premises and made to rest in a well ventilated area.
Should the patient feel unwell, OBTAIN MEDICAL ATTENTION

SECTION 5: Fire-fighting measures

•Recommended extinguishers: Water, CO2, Foam, Chemical powders, according to the materials involved in the fire.
•Extinguishers not to be used: None in particular.
•Risks arising from combustion: Avoid inhaling the fumes.
•Protective equipment: Use protection for the respiratory tract.

SECTION 6: Accidental release measures

•Measures for personal safety: Use gloves and protective clothing. In the event of particulates aerosols use respiratory protection.

•Environmental measures: .

Keep away from drains, surface- and ground-water and soil

•Cleaning methods:

Limit leakages with earth or sand. If the product has escaped into a water course, into the drainage system, or has contaminated the ground or vegetation, notify the competent authorities.
Remove the waste materials with a suitable device (for instance a suction pump) and dispose.
After the product has been recovered, rinse the area and materials involved with water.

SECTION 7: Handling and storage

•Handling precautions:

Wear suitable gloves, glasses and face protection. Avoid contact and inhalation of the vapours/powders.
Do not eat or drink while working.

•Incompatible materials:

None in particular.

•Storage conditions:

Always keep the containers tightly closed.

•Instructions as regards storage premises:

Adequately ventilated premises.

SECTION 8: Exposure controls / personal protection

| | <u>ACGIH-TLVs</u> | <u>OSHA PELs</u> | <u>NOISHA RELs</u> |
|------------------------------------|---|-----------------------|-------------------------|
| Tin Oxide (as Sn) (Total Dust) | 2.0 mg/m ³ | 2.0 mg/m ³ | 2.0 mg/m ³ |
| Chromium (III) Compounds (as Cr) | 0.5 mg/m 0.5 mg/m ³ | | 0.5 mg/m ³ |
| Iron Oxide Fume | 5 mg/m ³ 10 mg/m ³ | | 5 mg/m ³ |
| Cobalt, Metal, Dust & Fume (as Co) | 0.02 mg/l 0.5 mg/m ³ 5 mg/m ³ (respirable) | | N/A |
| Nickel, Metal (as Ni) | 0.2 mg/m 1 mg/m ³ | | 0.015 mg/m ³ |
| Tin Oxide (as Sn) (Total Dust) | 2.0 mg/m 2.0 mg/m ³ | | 2.0 mg/m ³ |

Safety glasses with side-shields (frame goggles) (EN 166)

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Due to the colouring properties of the product closed work clothes should be used, to avoid stains during manipulation. Hands and/or face should be washed before breaks and at the end of the shift.

| | |
|---|--------------|
| Appearance/form | Black/Powder |
| Odor | None |
| SPECIFIC GRAVITY | 4.93 |
| pH | 6 |
| Melting point/freezing point | >1000 C |
| Initial boiling point and boiling range | NA |
| Flash point | NA |
| Evaporation rate | NA |
| Flammability (solid, gas) | none |
| Upper/lower flammability limits | NA |
| Upper/lower explosive limits | NA |
| Vapor pressure | NA |
| Vapor density | NA |
| Relative density | NA |
| Solubility(ies) | insoluble |
| Partition coefficient: n-octanol/water | NA |
| Auto-ignition temperature | NA |
| Decomposition temperature | NA |
| Viscosity | NA |
| Explosive properties | none |
| Oxidizing properties | none |

SECTION 10: Stability and reactivity

Chemical stability

STABLE

Possibility of hazardous reactions

WILL NOT OCCUR

Incompatible materials NONE

Hazardous decomposition products N/A

SECTION 11: Toxicological information

ORAL LD50 (male rats) > 10000 mg/kg
INHALATION LC50 (rats; 4 hours) > 5.05 mg/L air (actual concentration)
SKIN N/A

NON IRRITATING TO THE SKIN
NON IRRITATING TO THE EYES

THIS PIGMENT IS NOT LISTED IN THE NATIONAL TOXICOLOGY PROGRAM (NTP) REPORT ON CARCINOGENS.
IT IS NOT LISTED AS A POTENTIAL CARCINOGEN IN THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER(IARC) MONOGRAPHS.
IT IS NOT FOUND TO BE A CARCINOGEN BY THE OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION(OSHA)

SECTION 12: Ecological information

ECOTOXICITY NO DATA
DEGRADABILITY NO DATA
MOBILITY NO DATA
BIOACCUMULATIVE NO DATA

SECTION 13: Disposal considerations

Disposal of the product Contain spillage and scoop or vacuum. Avoid making dust
put in appropriate container for disposal. Waste disposal method in accordance with
Federal, State and Local Laws.

Disposal of contaminated packaging Dispose of as unused product.

Waste treatment MUST BE PROCESSED THROUGH IN-HOUSE TREATMENT

Sewage disposal AVOID CITY DRAINS

SECTION 14: Transport information

| | |
|--|------|
| 14.1 UN Number | None |
| 14.2 UN Proper Shipping Name | None |
| 14.3 Transport hazard class(es) | None |
| 14.4 Packing group | None |
| 14.5 Environmental hazards | None |
| 14.6 Special precautions for user | None |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code | None |

SECTION 15: Regulatory information

California Prop 65 - WARNING! A chemical known to the State of
California to cause cancer was used to produce this product

Cobalt (II) Oxide
Nickel oxide

TSCA Inventory CAS #
18282-10-5
68186-97-0

Attention all Retailers of Mason Stains

ALL retailers of this product are REQUIRED by law to supply their customers with a copy of material safety data sheet with initial purchase.

*****SARA 313**

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (**SARA**) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CFR, Part 372.

The information contained in this SDS must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY! SDS'S ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.

Disclaimer

SECTION 16: REFERENCE INFORMATION

CPMA CLASSIFICATION AND CHEMICAL DESCRIPTIONS OF THE COMPLEX INORGANIC COLOR PIGMENTS
Fourth Edition - January 2013 Update

<https://www.osha.gov/index.html>

<http://chem.sis.nlm.nih.gov/chemidplus>

13th Report on Carcinogens on October 2, 2014.

<http://monographs.iarc.fr/ENG/Classification/index.php>

